

Description: BOPP Carton Sealing

PRODUCT NO.	Backing Material	Color	Adhesive	Total Thickness (micro)	Backing Thickness (micro)	Tensile Strength (N/in)	Adhesion (N/25mm)	Elongation (%)
B36	BOPP Packing Tape	Clear & Tan & Black & Yellow & Green & Blue & Red.	Water Based Acrylic	36	23	≥60	6.0	100---180%
B38				38	23	≥60	6.2	100---180%
B40				40	23	≥60	6.5	100---180%
B42				42	23	≥60	6.7	100---180%
B44				44	25	≥70	6.8	100---180%
B45				45	25	≥70	7.0	100---180%
B47				47	28	≥75	7.2	100---180%
B50				50	28	≥75	7.5	100---180%
B52				52	28	≥75	7.8	100---180%
B55				55	36	≥80	8.0	100---180%
B57				57	36	≥80	8.2	100---180%
B60				60	36	≥80	8.5	100---180%

TEST METHOD:

THICKNESS: ASTM-D5199

TACK¹: PSTC-6

TACK²: J.DOW.METHODS

PEEL: 180° ADEHESION TO STEEL, PSTC-1

HOLDING POWER: SHEAR TO STEEL, 1" x 1" x 1KG, 178°, PSTC-7

TENSILE & ELONGATION: PSTC-31

TESTING WERE CARRIED OUT IN 23±2°C AND 65±5%RH.

color swatch



Color #

T1

T2

T3

T4

color swatch



Color #

C1

C2

C3

C4

C5



An American owned manufacturing in Mainland China

Designer / Manufacturer of equipments with accessories for adhesive tape industries and supply Adhesive Tapes

Head Office: P.O. Box 1547 • 1000 Corporate Center Drive, Monterey Park, California 91754, USA

http://www.otape.com • email: sales@otape.com • Toll Free: 1-877-302-8981 • Fax: 1-877-302-8981

Office in China: 2103, No. 7, Lane 89, An-Shun Road, Chang Ning District, Shanghai 200052, China

Tel: +86-21-52306651 • Fax: +86-21-52306651 • 24 Hour Hotline: +86-13915497733 • email: info@otape.com

Plant 1: 6, Shang Yu Road, Industrial Park District, Shu Yang, Jiangsu 223600, China

Plant 2: 8, Xinyi Road. Economic Development Zone, Jingjiang, Jiangsu 214500, China

Distribution in Sri Lanka: 164 Puttalam Road, Kurunegala, Sri Lanka