

## Specifications

**1. Standard model : OT-S2002 OPP Adhesive Tape Slitter+Rewinder**

**2. Application :** 4 shafts auto turret exchange, suitable for slitting/rewinding OPP packaging & stationery tapes.

**3. Feature:**

- (1). Equipped with connected unwind base, which is convenience on operation and space saving.
- (2). Equipped with surface type lay on roller on unwind base to make web wound out more smoothly.
- (3). Slitting by razor blade, which was designed to slit various film tapes.
- (4). Driven by one A.C motor with 3 stages type length counter to make machine stops accurately.
- (5). Rewind tension is controlled by clutch, it works with differential shafts to make tension on each roll the same even when the web thickness is not the same at all.
- (6). Finished rolls unload and paper cores reload working by core loader, it increases full production capacity.

**4. Optional Part:**

Core Alum — Mold: It is needed when slitting different sizes, any sizes can be made on your request.

**5. Specification:**

Machine Width	1.3M/1.6 M	Max. Unwind O.D	Ø800 mm
Machine Speed	0~180 M/min	Mini. Slitting Width	24 mm
Rewind Paper Core	Ø77 mm(3")	Blade	Razor Blade (0.2x22x60mm)
Max. Rewind O.D	Ø150 mm( 4 shafts exchange)		



Images and specifications may not represent the exact product associated with above picture and information provided in this document pertain to O-Tape brand products and are subject to change at any time, without notice.

**An American owned manufacturing in Mainland China**

**Designer / Manufacturer of Converting Equipments with accessories for adhesive tape industries and supply Adhesive Tapes**

Plant: 6 Shang Yu Road, Industrial Park District, Shu Yang, Jiangsu 223600, P.R. China

Tel: +86-527-3966217 • Fax: +86-527-3966258 • 24 Hour Hotline: +86-13871098656 • email: [china@otape.com](mailto:china@otape.com)

Office in USA: P.O. Box 1547 • 1000 Corporate Center Drive, Monterey Park, California 91754

<http://www.otape.com> • Toll Free: 1-877-302-8981 • Fax: 1-877-302-8981 • email: [sales@otape.com](mailto:sales@otape.com)