

Specifications

1. Standard model : OTS2002B Super Clear OPP Tape Slitter Rewinder

2. Application : Specialized in producing super clear adhesive tape. 4 shafts auto turret exchange. The equipment uses unique rewinding pressure roll. During rewinding, the rewinding roll keep in touch with the pressure roll to avoiding the air into the rewinding film, so it can manufacture super clear production with high-speed rewinding.

3. Feature:

- (1). Equipped with connected unwind base, which is convenience on operation and space saving.
- (2). Equipped with surface type lay on roller on unwind base to make web wound out more smoothly.
- (3). Slitting by razor blade, which was designed to slit various film tapes.
- (4). Driven by one A.C motor with 3 stages type length counter to make machine stops accurately.
- (5). Rewind tension is controlled by clutch, it works with differential shafts to make tension on each roll the same even when the web thickness is not the same at all.
- (6). Finished rolls unload and paper cores reload working by core loader, it increases full production capacity.
- (7). Unique rewinding pressure roll: rubber pressure roll, unique push by cylinder.

4. Optional Part:

1. Core Alum — Mold: It is needed when slitting different sizes, any sizes can be made on your request.
2. Tabbing Device: Automatic tabbing on the web during the production.

5. Specification:

Machine Width	1.3 M	Max. Unwind O.D	Ø800 mm
Machine Speed	0~180 M/min	Slitting Width	48 mm / 60 mm
Rewind Paper Core	Ø77 mm(3")	Blade	Razor Blade(0.2x22x60mm)
Max. Rewind O.D	Ø150 mm(4 shafts exchange)		



Images and specifications may not represent the exact product associated with above picture and information provided in this document pertain to O-Tape brand products and are subject to change at any time, without notice.

An American owned manufacturing in Mainland China

Designer / Manufacturer of Converting Equipments with accessories for adhesive tape industries and supply Adhesive Tapes

Plant: 6 Shang Yu Road, Industrial Park District, Shu Yang, Jiangsu 223600, P.R. China

Tel: +86-527-3966217 • Fax: +86-527-3966258 • 24 Hour Hotline: +86-13871098656 • email: china@otape.com

Office in USA: P.O. Box 1547 • 1000 Corporate Center Drive, Monterey Park, California 91754

<http://www.otape.com> • Toll Free: 1-877-302-8981 • Fax: 1-877-302-8981 • email: sales@otape.com