

## Specifications

**1. Standard model : OTS3320 Duplex Center Surface Slitter Rewinder**

**2. Application :** 2 shafts center-surface type winding, suitable for slitting various OPP films, Paper...etc.

**3. Feature:**

- (1). Equipped with separated shaft type unwind base and auto unwind tension controller.
- (2). Driven by connective 3 A.C motors, able to control tension on air shaft and linear speed on differential shaft.
- (3). Equipped different shafts to make tension on each roll the same even when the web thickness is not the same.
- (4). Equipped with shear cutter, which is suitable for slitting various materials and trim unit is as strong blower.

**4. Optional Part:**

- (1). Special Unwind Base : Separated type with hydraulic core chuck can be equipped for efficient and quick performance on jumbo roll change.
- (2). Connected Splice Table : Splicing materials smoothly in order to decrease production loss.

**5. Specification:**

Machine Width	1.3 M / 1.6 M	Max. Unwind O.D	Ø1000 mm
Min.Slitting Width	25 mm	Rewind Core I.D	3" (Ø76.2 mm )
Max.Rewind O.D	Ø650 mm	Machine Speed	0-200 M/min



Images and specifications may not represent the exact product associated with above picture and information provided in this document pertain to O-Tape brand products and are subject to change at any time, without notice.

**An American owned manufacturing in Mainland China**

**Designer / Manufacturer of Converting Equipments with accessories for adhesive tape industries and supply Adhesive Tapes**

Plant: 6 Shang Yu Road, Industrial Park District, Shu Yang, Jiangsu 223600, P.R. China

Tel: +86-527-3966217 • Fax: +86-527-3966258 • 24 Hour Hotline: +86-13871098656 • email: [china@otape.com](mailto:china@otape.com)

Office in USA: P.O. Box 1547 • 1000 Corporate Center Drive, Monterey Park, California 91754

<http://www.otape.com> • Toll Free: 1-877-302-8981 • Fax: 1-877-302-8981 • email: [sales@otape.com](mailto:sales@otape.com)