

Specifications

1. Standard model : OTS501 Duplex Surface Slitter Rewinder

2. Application : 2 shafts surface type winding, suitable for slitting various papers.

3. Feature:

- (1). Equipped with separated shaft type unwind base, auto web guide and auto unwind tension controller.
- (2). Slitting by shear cutter, which was designed for slitting various papers.
- (3). Driven by one A.C motor with 2 stages type length counter to make machine stops accurately.
- (4). Rewind tension is as surface friction type, working with auto unwind tension controller to make perfect winding on all finished rolls.
- (5). Trimming unit is as suction blower, which has high performance and quick collecting for waste materials.

4. Optional Part:

Special Unwind Base : Separated type with hydraulic core chuck can be equipped for efficient and quick performance on jumbo roll change.

5. Specification:

Machine Width	1.0 M / 1.3 M / 1.6 M	Max. Unwind O.D	Ø1000 mm
Min.Slitting Width	25 mm	Rewind Core I.D	3" (Ø76.2 mm)
Max.Rewind O.D	Ø1000 mm	Machine Speed	0-200 M/min



Images and specifications may not represent the exact product associated with above picture and information provided in this document pertain to O-Tape brand products and are subject to change at any time, without notice.

An American owned manufacturing in Mainland China

Designer / Manufacturer of Converting Equipments with accessories for adhesive tape industries and supply Adhesive Tapes

Plant: 6 Shang Yu Road, Industrial Park District, Shu Yang, Jiangsu 223600, P.R. China

Tel: +86-527-3966217 • Fax: +86-527-3966258 • 24 Hour Hotline: +86-13871098656 • email: china@otape.com

Office in USA: P.O. Box 1547 • 1000 Corporate Center Drive, Monterey Park, California 91754

<http://www.otape.com> • Toll Free: 1-877-302-8981 • Fax: 1-877-302-8981 • email: sales@otape.com