

## Specifications

**1. Model: OTSK Duplex Center Surface Slitter Rewinder**

**2. Application:** 2 shafts center-surface type winding, suitable for slitting various OPP, PET, PVC, printing & packing films etc.

**3. Feature:**

- (1). Equipped with connected shaft type unwind base and automatic web guide.
- (2). Unwind tension is automatically controlled by powder brake when jumbo roll O.D is getting smaller.
- (3). Rewind shaft tension is controlled by differential core sleeve; each of slipping tension is adjustable automatically and individually to control perfect rewind tension on all finished rolls when web thickness is not even the same.
- (4). It equipped with surface type of rewind pressure roller to making finished rolls for better smooth and flat.
- (5). It slitting with shear cutter.

**4. Optional Part:**

- (1). Special Unwind Base: Separated type with hydraulic core chuck can be equipped for efficient and quick performance on jumbo roll change.
- (2). Slitting by shear cutter and razor blade, which were designed for multi-purpose materials converting propose.

**5. Specification:**

Machine Width	1.0 M / 1.3 M / 1.6 M	Max. Unwind O.D.	Ø800 mm
Min. Slitting Width	50 mm	Rewind Core I.D.	3" (Ø76.2 mm )
Max. Rewind O.D.	Ø400 mm	Machine Speed	0-200 M/min



Images and specifications may not represent the exact product associated with above picture and information provided in this document pertain to O-Tape brand products and are subject to change at any time, without notice.

**An American owned manufacturing in Mainland China**

Designer / Manufacturer of equipments with accessories for adhesive tape industries and supply Adhesive Tapes

Head Sales Office in USA: P.O. Box 1547 • 1000 Corporate Center Drive, Monterey Park, California 91754

Toll Free: 1-877-302-8981 • Fax: 1-877-302-8981 • <http://www.otape.com> • email: [sales@otape.com](mailto:sales@otape.com)

Plant: 6 Shang Yu Road, Industrial Park District, Shu Yang, Jiangsu 223600, P.R. China

Tel: +86-527-83966217 • Fax: +86-527-83966258 • 24 Hour Hotline: +86-13915497733 • <http://www.otape.com> • email: [otape@earthlink.net](mailto:otape@earthlink.net)